



creating
solutions
together

Drum Washer 350 UST Ultrasonic - Demo

Why Customers Choose Ultrasonic Cleaning

Ultrasonic cleaning uses high-frequency sound waves in liquid to remove contaminants, resulting in:

- Effective cleaning of parts with holes and cavities
- Thorough cleaning of complex geometries
- Gentle process without mechanical wear
- Ideal for components with high cleanliness requirements



Standard Equipment

- Siemens PLC
- Grundfos pump
- Fully insulated construction
- Automatic level and pressure monitoring

Optional Features

- Oil separator
- Filtration system
- Automatic chemical dosing
- Adjustable drum speed
- Integration with existing production lines
- Remote access and service via network connection
- Service and spare parts agreement

An Environmentally Responsible Choice

- Manufactured in Denmark
- High-quality components
- Recyclable materials
- Reduced chemical consumption
- Energy optimization

Design Philosophy

- Modular design
- Service-friendly construction
- Reliable operation
- Energy efficient
- Durable construction
- Cost-effective operation
- Recyclable materials

Technical Data

General

Length	3000 mm
Width	1130 mm
Height	1260 mm
Weight	725 kg
Power supply	3 x 400 V / 50 hz + N + PE
Consumption	57 A

Drum

Diameter	500 / 300 mm
Speed	1-5 rpm
Perforation	2-10 mm

Washing zone

Flow rate	100 L/min
Tank volume	210 L
Temperature	30-60°C
Heating power	12 kW
Ultrasound power	3 kW

Rinsing zone

Flow rate	200 L/min.
Tank volume	210 L

Drying zone

Airflow	3500 L/min
Temperature	40-110°C

Contact Us

KSN Industry A/S • Bjerring Hede 12 • 8850 Bjerringbro
+45 86 68 03 00 • ksn@ksn.dk • www.ksnindustry.com